

MastaCoat3

JOINTING COMPOUND



TECH DATA

MastaCoat3 is an all purpose jointing compound suitable for bedding tape, second and final coating plasterboard joints. MastaCoat3 is premixed and ready to use. It is ideal in renovations and smaller jobs such as maintenance and prepaint repairs.



Performance

Body

Exceptional body and ease of trowelling.

Drying

The perfect amount of time to obtain good thin edges when feathering as it does not dry out too fast.

Colour

A dark brown colour when applied making it easy to determine progress of jointing. The change in colour as MastaCoat3 dries ensures sanding is commenced only when the joints are completely dry. The dark colour is also useful for identifying patches for sanding, following minor repairs to walls at the completion of the job.

Sanding

Quick and very easy to sand. Leaves a finish which is free from scratches.

Sustainable

Low VOC meeting sustainable building project requirements.

Benefits

- > Premixed for easy use
- > Easy to clean
- > Minimal wastage

Product Information

SIZE	4kg bucket		
TYPE	Light weight air drying premixed all purpose compound		
DRYING TIME	24 hours		
SYSTEM USAGE	<input checked="" type="checkbox"/> Bedding	<input checked="" type="checkbox"/> Second coat	<input checked="" type="checkbox"/> Final coat
	<input checked="" type="checkbox"/> Standard		
SPECIFIC DENSITY	1.2g/cc		

MastaCoat3

JOINTING COMPOUND



TECH DATA

Application

- MastaCoat3 is ready to use for hand trowelling.
- If mixing MastaCoat3, note that overmixing may introduce air bubbles.
- As with all compounds, excessive thinning may cause cracking or increased shrinkage. Do not mix with any other material.
- Maintain a minimum 10°C working temperature during application and drying.
- When using MastaCoat3 as an all purpose, ensure all joints are back-blocked. Fibreglass tape can be used with MastaCoat3.
- Allow MastaCoat3 to dry completely between coats and approximately 24 hours before sanding.
- Sand lightly by hand using 150 grit paper or 180 sanding mesh. When using an electric sander use 220 grit paper.
- MastaCoat3 will accept most types of decorative finishes. In accordance with AS/NZS 2311 *Guide to the painting of buildings*, a three coat paint system must be used. This consists of a sealer/undercoat and two coats of paint.

Optimise product performance by:

- Firmly closing the lid to prevent the compound from drying out.
- Washing tools before product dries and hardens.
- Storing in a dry, well ventilated environment fully protected from the weather.



Quality
ISO 9001

SAI GLOBAL

Knauf products manufactured in Australia are produced in accordance with quality systems certified as complying with AS/NZS ISO 9001:2008.

Warranty

Knauf's products are guaranteed by a 10 Year Warranty. Visit knaufplasterboard.com.au for details.

Technical Advice

For technical advice, please call Knauf technical services on **1300 724 505**.